

ResinDek® Mezzanine Floor Panels




Finishes Available

| Product Name | Live Dead Pallet Jack Limits | Thickness | Unfinished | GDS, CDS | ESD |
|-----------------------------|---------------------------------|-----------|------------|----------|-----|
| ResinDek® XLD ₅₀ | up to 1,250 lbs | 1/2" | ■ | ■ | ■ |
| ResinDek® LD ₅₀ | up to 2,000 lbs | 1/2" | ■ | ■ | ■ |
| ResinDek® LD | up to 2,000 lbs. | 3/4" | ■ | ■ | ■ |
| ResinDek® MD | up to 3,000 lbs. | 3/4" | n/a | ■ | ■ |
| ResinDek® HD | up to 4,500 lbs. | 3/4" | n/a | ■ | ■ |
| ResinDek® MAX | Up to 8,000 lbs. | 1-1/2" | n/a | ■ | ■ |
| ResinDek® Xspan® | Up to 3,000 lbs - No Corrugated | 1-1/8" | n/a | ■ | ■ |

Finishes Available

Gray Diamond Seal®
Clear Diamond Seal®
ESD Certified Static Control

Options

Invisi-Loc® fasteners
T & G Configurations
No Added Formaldehyde 

All ResinDek Products can contribute towards earning points for LEED® qualified buildings.