

While a ResinDek<sup>®</sup> floor provides long-lasting durability, safety and cleanability, it must be properly installed and maintained to avoid costly floor problems, repairs and hazards that may potentially void all product warranties.

Whether your ResinDek<sup>®</sup> floor finish is Clear Diamond Seal<sup>®</sup>, Gray Diamond Seal<sup>®</sup> or ESD, the surface can be easily cleaned using a damp mop or standard cleaning solvents without fear of damaging the surface. Cleaning solutions that have worked particularly well include water, diluted isopropyl alcohol, and many off the shelf detergents and floor cleaners. **Never use methylene chloride or paint thinners, which will damage ResinDek finishes. Also avoid prolonged soaking, hosing down, or wetting of all ResinDek products.**

**ResinDek UF (unfinished) will clean up similar to other unfinished wood products.**

For touching up surface blemishes and scratches on your ResinDek Gray Diamond Seal or ESD finish, a can of color-matched spray paint can be obtained from Cornerstone Specialty Wood Products.

When using the touch-up paint, be sure to shake the spray can for at least 60 seconds for proper color mixing. For best results, spray using repeated, light coats of paint and

allow adequate drying time before resuming floor traffic.

**Read all touch-up paint manufacturer labels and warnings before using resin-based products and work in a fully ventilated area with proper protection for eyes and hands.**

For repairing deeper cracks or holes in ResinDek panel surfaces, it is possible to use standard fiberglass or polymer resin patch compound commonly used in auto body repair.

To repair a damaged ResinDek panel surface, mix an appropriate amount of hardener and resin and apply the mixture into the damaged area, as directed. Use a putty knife to spread and skim the surface smooth before the material hardens. Depending on the depth and size of the damaged area, more than one application may be required to build up the patch material at or above the ResinDek surface level. Allow adequate drying time as directed.

After drying, use 80 grit sandpaper to sand the resin patch flush with the ResinDek panel surface. Feather sand the area, taking care not to damage the surrounding ResinDek panel finish.

After sanding the repaired area, apply touch-up paint as instructed earlier in this video module. If painting reveals that the

patched surface is not flat, it may be necessary to sand and repaint the area again.

If you have additional questions about repairing ResinDek panels, contact Cornerstone Specialty Wood Products at 1- 888-755-3048 or send an e-mail to [info@resindek.com](mailto:info@resindek.com).

### DVD available upon request



## ResinDek<sup>®</sup> Panels are Available in Three Finishes:

| Panel Name   | Live/Dead Pallet Jack Limits | Finishes | Gray Diamond Seal <sup>®</sup> | Clear Diamond Seal <sup>®</sup> | ESD | Unfinished |
|--|------------------------------|----------|--------------------------------|---------------------------------|-----|------------|
| ResinDek <sup>®</sup> LD   | Up to 2,000 lbs              |          | ■                              | ■                               | ■   | ■          |
| ResinDek <sup>®</sup> MD   | Up to 3,000 lbs              |          | ■                              | ■                               | ■   |            |
| ResinDek <sup>®</sup> HD   | Up to 4,500 lbs              |          | ■                              | ■                               | ■   |            |
| ResinDek <sup>®</sup> Xspan <sup>®</sup><br>(no corrugated required) | Up to 3,000 lbs, 16" O.C.*   |          | ■                              | ■                               | ■   |            |
| ResinDek <sup>®</sup> EF   | Up to 1,500 lbs              |          | ■                              | ■                               | ■   |            |

\*Actual allowable load varies with span, contact Cornerstone Specialty Wood Products for details.



**the best in the industry!**

All ResinDek Products can contribute towards earning points for LEED<sup>®</sup> qualified buildings.



[www.resindek.com](http://www.resindek.com)

©2007 Cornerstone Specialty Wood Products, LLC<sup>TM</sup>  
All rights reserved. Cornerstone Specialty Wood Products, LLC, the Cornerstone logo, the 7-year warranty logo, ResinDek, The Panel of Experts, Xspan, Diamond Seal and Invisi-Loc are trademarks of Cornerstone Specialty Wood Products, LLC<sup>TM</sup>.