



## ResinDek<sup>®</sup> 7-Year Product Warranty

Cornerstone Specialty Wood Products, LLC<sup>TM</sup> (CSWP) hereby warrants all of its ResinDek<sup>®</sup> panels to be free from defect, structurally sound, and able to safely carry the specified design loads as specified. At its option, CSWP will either replace or make a reasonable allowance for repair to all ResinDek Panels found to be defective for a period of seven (7) years from date of shipment to the jobsite.

### Qualifications to this warranty are as follows:

1. All panels must be installed in accordance with ResinDek Installation Instructions.
2. All panels must be properly unloaded, protected and stored prior to their installation. Care shall be taken to protect the panels from excessive moisture before, during, and after installation.
3. ResinDek<sup>®</sup> XLD<sub>50</sub>, LD<sub>50</sub>, LD, MD, HD & ResinDek<sup>®</sup> Max panels must be installed with only CSWP approved fasteners over the gauge and type of corrugated metal decking for the load on the floor as approved by CSWP.

4. ResinDek Xspan<sup>™</sup> must be supported at intervals approved by CSWP with structural supports capable of withstanding loads imposed. Fastener number, pattern and type must be approved by CSWP.
5. Do Not Exceed the (live and dead load) pallet jack loads as follows per specified panel:
  - ResinDek<sup>®</sup> XLD<sub>50</sub> 1,250 lbs. max.
  - ResinDek<sup>®</sup> LD<sub>50</sub> 2,000 lbs. max.
  - ResinDek<sup>®</sup> LD 2,000 lbs. max.
  - ResinDek<sup>®</sup> MD 3,000 lbs. max.
  - ResinDek<sup>®</sup> HD 4,500 lbs. max.
  - ResinDek<sup>®</sup> MAX 8,000 lbs. max.ResinDek Xspan<sup>®</sup> Do not exceed CSWP recommended loads as stated on Xspan<sup>®</sup> specifications.
6. Allowable loads are based on testing conducted by CSWP with 36" o.c. spans on ResinDek<sup>®</sup> XLD<sub>50</sub>, LD<sub>50</sub>, LD, MD, HD, & ResinDek<sup>®</sup> Max. Longer spans may reduce load carrying capacities. Refer to ResinDek<sup>®</sup> Xspan<sup>®</sup> literature for allowable point loads, uniform loads, & live and dead pallet jack loads for ResinDek Xspan<sup>®</sup>.

7. CSWP must be notified in the event of a problem with any of its materials, and given a minimum of two weeks notice to correct the problem on its own, and/or personally visit the site if necessary, prior to repairs and remedies by others.
8. There will be no warranty coverage for acts of God, exposure to weather, or for impact or concentrated loads.
9. This warranty will be considered void in the event of prolonged exposure to standing water on the ResinDek panels.
10. There will be no warranty coverage for acts of negligence by the installer, the customer, or the end user.
11. This warranty is between CSWP and its customer. Warranty will flow through to the end user for the entire period of this warranty.



**CORNERSTONE**  
SPECIALTY WOOD PRODUCTS, LLC<sup>™</sup>

10179 Wayne Avenue  
Cincinnati, OH 45215  
Toll Free: 888.755.3048  
Tel: 513.772.5560  
Fax: 513.772.5561  
[www.resindek.com](http://www.resindek.com)