

## 1. Which type of mezzanine flooring should you select for your needs?

Look at the chart below to see a summary of product strengths and weaknesses:

Rank of Products: 6 = Best, 1 = Worst Rating

	Plywood OSB	Plywood/OSB with HDPE Laminate	Bar Grate	Concrete	UV Coated Particle Board	ResinDek <sup>®</sup>
Material Cost	6	3	2	1	4	5
Wheel Load Cap	1	2	4	6	3	5
Tolerances	2	1	4	3	6	6
Delamination Resistance	1	2	6	6	6	6
Scratch Resistance	1	4	6	5	2	3
ESD Issues	4	1	5	3	2	6
Cleanability	1	3	6	4	3	6
Warranty	1	4	1	1	4	6
Price Volatility	2	3	1	5	5	5
Customer Satisfaction	1	2	4	4	4	6
<b>Total Score</b>	<b>20</b>	<b>26</b>	<b>39</b>	<b>38</b>	<b>39</b>	<b>55</b>

## 2. Which ResinDek product grade is right for your application?

ResinDek Panels Are Available in 4 Grades:

Panel Grade	Live & Dead Pallet Jack Loads Permitted
ResinDek <sup>®</sup> LD	Foot Traffic and up to 2,000 lbs. Total Load
ResinDek <sup>®</sup> MD	Foot Traffic and up to 3,000 lbs. Total Load
ResinDek <sup>®</sup> HD	Foot Traffic and up to 4,500 lbs. Total Load
ResinDek <sup>®</sup> Xspan <sup>®</sup> (no corrugated required)	16" (on center) o.c. up to 3,000 lbs 24" o.c. 2,700 lbs. 32" o.c. 2,300 lbs 40" o.c. 2,000 lbs.

## 3. Which ResinDek product finish is right for your application?

Jobsite Requirement	Gray Diamond Seal <sup>®</sup>	Clear Diamond Seal <sup>®</sup>	ResinDek <sup>®</sup> ESD	ResinDek <sup>®</sup> Unfinished (UF)
Cleanable Surface	X	X	X	
Superior Stain Resistance	X	X	X	
Skid Resistant Surface	X	X	X	
Showcase Look	X	X	X	
High Gloss Floor	X	X	X	
Superior Scratch Resistance	X	X	X	
Economical Finish	X	X		
Warranty	X	X	X	X
Static Controlled Floor			X	

## ResinDek<sup>®</sup> Panels are Available in Three Finishes:

Panel Name	Live/Dead Pallet Jack Limits	Finishes
ResinDek <sup>®</sup> LD	Up to 2,000 lbs	 Gray Diamond Seal <sup>®</sup> Clear Diamond Seal <sup>®</sup> ESD   Unfinished
ResinDek <sup>®</sup> MD	Up to 3,000 lbs	Gray Diamond Seal <sup>®</sup> Clear Diamond Seal <sup>®</sup> ESD
ResinDek <sup>®</sup> HD	Up to 4,500 lbs	Gray Diamond Seal <sup>®</sup> Clear Diamond Seal <sup>®</sup> ESD
ResinDek <sup>®</sup> Xspan <sup>®</sup> (no corrugated required)	Up to 3,000 lbs, 16" O.C.*	Gray Diamond Seal <sup>®</sup> Clear Diamond Seal <sup>®</sup> ESD
ResinDek <sup>®</sup> <b>EF</b>	Up to 1,500 lbs	Gray Diamond Seal <sup>®</sup> Clear Diamond Seal <sup>®</sup> ESD

\*Actual allowable load varies with span, contact Cornerstone Specialty Wood Products for details.



**the best in the industry!**

All ResinDek Products can contribute towards earning points for LEED<sup>®</sup> qualified buildings.



[www.resindek.com](http://www.resindek.com)