

ResinDek[®] Xspan[®] offers the look, maintainability and performance of ResinDek in a structural flooring solution where a corrugated metal substructure is not required in certain applications.

- Extensively tested and capable of safely supporting 125 psf dead loads at 32" center supports and 2,300 lbs pallet jack loads without corrugated metal B deck. Please refer to the table below for ResinDek Loads and Spans for allowable point loads, uniform loads and pallet jack live and dead loads.
- Available in Clear Diamond Seal[®], Gray Diamond Seal[®] and ESD finishes.
- Variety of lengths, widths and tongue and groove configurations offered to fit custom aisles and storage rack applications.

ResinDek Xspan flooring panels have been approved by IBC Code Officials for use as a structural flooring system in certain applications. Structural supports must be reviewed and approved by Cornerstone Specialty Wood Products and must be capable of supporting the floor loads at the specified intervals. **For further details, check with Cornerstone Specialty Wood Products and/or your local building code officials.**



ResinDek Xspan Load Span Tables

Type of Load	Unit of Measure	Span (inch / Allowable Load)			
		16	24	32	40
Hand Pallet Truck Loads:	Lbs	3,000	2,700	2,300	2,000
Uniform Loads:	Lbs/Ft ²	375	225	125	75
Point Loads on Plates:					
Plate Size (inch)					
2 x 2	Lbs	676	616	540	317
3 x 3	Lbs	737	646	575	350
4 x 4	Lbs	785	686	620	365
5 x 5	Lbs	820	705	635	384
6 x 6	Lbs	935	806	700	402



www.resindek.com