

While a ResinDek[®] floor provides long-lasting durability, safety and cleanability, it must be properly installed and maintained to avoid costly floor problems, repairs and hazards that may potentially void all product warranties.

Whether your ResinDek[®] floor finish is Gray Diamond Seal 2[™], ESD or TriGard[™], the surface can be easily cleaned using a damp mop or standard cleaning solvents without fear of damaging the surface. Cleaning solutions that have worked particularly well include water, diluted isopropyl alcohol, and many off the shelf detergents and floor cleaners. **Never use methylene chloride, degreasers or paint thinners which will damage ResinDek finishes. Also avoid prolonged soaking, hosing down, or wetting of all ResinDek products.**

ResinDek UF (unfinished) will clean up similar to other unfinished wood products.

**All cracks and holes should be investigated since these are primarily due to loads in excess of ResinDek[®] recommendations.*

Excessive load damage to ResinDek[®] panels cannot always be repaired, and may need to be replaced. Please contact us and we will be happy to assist you in determining the cause of the panel damage and how best to repair it in accordance with the ResinDek[®] Product Warranty.

For more information about repairing ResinDek panels, contact Cornerstone Specialty Wood Products at 1-888-755-3048 or send an e-mail to info@resindek.com.



ResinDek[®] Mezzanine Floor Panels



Product Name	Pallet Truck Load Limits **	Thickness	UF	Finishes Available		
				GDS2	ESD	TriGard [™]
ResinDek [®] LD	up to 2,000 lbs.	3/4"	■	■	■	■
ResinDek [®] SD	up to 2,500 lbs.	3/4"	■	■	■	■
ResinDek [®] MD	up to 3,500 lbs.	3/4"	n/a	■	■	■
ResinDek [®] HD	up to 4,500 lbs.	3/4"	n/a	■	■	■
ResinDek [®] MAX	up to 8,000 lbs.	1-1/2"	n/a	■	■	■
* ResinDek [®] Xspan [®]	up to 3,000 lbs.	1-1/8"	n/a	■	■	■
* ResinDek [®] Xspan FR [®]	up to 3,800 lbs.	1-1/8"	n/a	■	■	■

Finishes Available

Unfinished
Gray Diamond Seal 2[™]
ESD Certified Static Control
TriGard[™]

Options

Invisi-Loc[®] fasteners
T & G Configurations
No Added Formaldehyde



All ResinDek Products can contribute towards earning points for LEED[®] qualified buildings.

* No Corrugated Required
** Includes Weight of Pallet Truck



www.resindek.com



12020 Tramway Drive
Cincinnati, OH 45241

Toll Free: 888.755.3048

Tel: 513.772.5560

Fax: 513.772.5561

www.resindek.com