



## ResinDek® SD Flooring Panels

### ResinDek SD Product Description

ResinDek SD is a 3/4" thick mezzanine flooring panel that is the perfect solution for supporting live and dead pallet jack loads up to 2,500 lbs. ResinDek SD floor panel is a value engineered flooring solution that will provide long-lasting durability, aesthetic appeal and is easy to maintain.

ResinDek panels are made with specially sorted and processed wood fibers, customized formaldehyde free resins, and a wax emulsifier. The ingredients are combined and compressed under extremely high pressure and temperature, resulting in a panel with superior physical properties that are especially designed and built to withstand heavy rolling cart and pallet jack loads.

ResinDek panels are certified to have no added Formaldehyde. ResinDek panels can contribute towards earning points for LEED® qualified buildings. When required ResinDek panels are available with FSC® Certification. FSC® License Code FSC-C124474.

### ResinDek SD Specifications

Mezzanine floor panels shall be ResinDek SD as manufactured by Cornerstone Specialty Wood Products. ResinDek SD shall be .75" in thickness and capable of supporting live and dead loads up to 2,500 lbs. ResinDek SD shall have a Gray Diamond Seal® 2 or optional ResinDek finish as provided by Cornerstone Specialty Wood Products.

### 10-Year Product Warranty

A 10-year warranty shall be provided and passed to the end user from the manufacturer. Installation of ResinDek panels shall be in accordance with the ResinDek Installation Instructions provided by Cornerstone Specialty Wood Products.



### Evaluation Service Report

ResinDek panels have been independently evaluated and approved for use in Types I-V construction, and as part of a fire-resistance rated assembly by the IAPMO Uniform Evaluation Services. United States ER Number 467. Canada ER Number UEL 5027.

### ResinDek Services

- CAD drawings that optimize materials
- Pre-job planning and on-site consultations
- Installation support for training
- Logistics support to coordinate deliveries
- Cut to size panels
- Testing for your specific loading conditions

### ResinDek Options

- Unfinished
- Gray Diamond Seal® 2 Finish
- ESD
- TriGard® Finish
- MetaGard® Steel Finish
- Invisi-Loc® Underside Fasteners
- Collated Screws
- Custom Tongue & Groove Configurations
- Eligible for LEED® Credits
- Available in sizes up to 4' x 10' (ResinDek with MetaGard max size is 4'x 8')

Product Name	Pallet Jack Load Limits **	Thickness	UF	Finishes Available			
				GDS2	ESD	TriGard®	MetaGard®
ResinDek® LD	up to 2,000 lbs.	3/4"	■	■	■	■	■
ResinDek® SD	up to 2,500 lbs.	3/4"	■	■	■	■	■
ResinDek® MD	up to 3,500 lbs.	3/4"	n/a	■	■	■	■
ResinDek® HD	up to 4,500 lbs.	3/4"	n/a	■	■	■	■
ResinDek® MAX	up to 8,000 lbs.	1-1/2"	n/a	■	■	■	■
* ResinDek® Xspan®	up to 3,000 lbs.	1-1/8"	n/a	■	■	■	■
* ResinDek® Xspan® FR	up to 3,800 lbs.	1-1/8"	n/a	■	■	■	■

**Finishes Available**  
Unfinished  
Gray Diamond Seal® 2  
ESD Certified Static Control  
TriGard®  
MetaGard®

**Options**  
Invisi-Loc® fasteners  
T & G Configurations

*All ResinDek Products can contribute towards earning points for LEED® qualified buildings.*  
\* No Corrugated Required  
\*\* Includes Weight of Pallet Jack

For detailed ResinDek SD Master Specifications please email or call Cornerstone Specialty Wood Products.

