

With our Electrostatic Dissipative Finish, ResinDek[®] ESD mezzanine floor panels provide an outstanding static control solution for mezzanine floors, shelving systems and workstations.

- ESD protection for electrically sensitive devices such as laptops, barcode scanners, servo-drive motors, and pick-to-light systems that are common in distribution centers
- Eliminate expensive computer downtime caused by electrostatic discharges
- Prevent uncomfortable static shocks to employees with a grounded surface
- Available on all panel grades of ResinDek

ResinDek[®] ESD panels have been extensively tested by the testing firm of Stephen Halperin & Associates and have been found to be in compliance with the following ESD Association Specifications:

ANSI/ESD S7.1

Resistive Characterization of Materials—Floor Materials.

ANSI/ESD S20.20

Protection of Electrical and Electronic Parts, Assemblies and Equipment.

ANSI/ESD STM97.1

Floor Materials and Footwear—Resistance

Measurement in Combination with a Person.

Testing Results are Summarized as Follows:

- Average point-to-point resistance = 6.6 x 10⁶ ohms
- Average point-to-ground resistance = 7.8 x 10⁶ ohms
- ResinDek[®] ESD mezzanine floor panels generated less than 10 volts with static controlled footwear, and experienced a rapid voltage decay from 5,000 volts to less than 50 volts in under .50 seconds

ResinDek ESD also provides a stain, scratch and skid resistant surface that won't delami-



nate like other decking materials. It installs easily over corrugated metal B-decking with recommended fastening systems.



ResinDek[®] Mezzanine Floor Panels



Product Name	Pallet Truck Load Limits **	Thickness	UF	Finishes Available		
				GDS2	ESD	TriGard™
ResinDek [®] LD	up to 2,000 lbs.	3/4"	■	■	■	■
ResinDek [®] SD	up to 2,500 lbs.	3/4"	■	■	■	■
ResinDek [®] MD	up to 3,500 lbs.	3/4"	n/a	■	■	■
ResinDek [®] HD	up to 4,500 lbs.	3/4"	n/a	■	■	■
ResinDek [®] MAX	up to 8,000 lbs.	1-1/2"	n/a	■	■	■
* ResinDek [®] Xspan [®]	up to 3,000 lbs.	1-1/8"	n/a	■	■	■
* ResinDek [®] Xspan FR [®]	up to 3,800 lbs.	1-1/8"	n/a	■	■	■

Finishes Available

Unfinished
Gray Diamond Seal 2™
ESD Certified Static Control
TriGard™

Options

Invisi-Loc[®] fasteners
T & G Configurations

All ResinDek Products can contribute towards earning points for LEED[®] qualified buildings.

* No Corrugated Required
** Includes Weight of Pallet Truck



www.resindek.com

©2017 Cornerstone Specialty Wood Products, LLC™
All rights reserved. Cornerstone Specialty Wood Products, LLC, the Cornerstone logo, the 10-year warranty logo, ResinDek, The Panel of Experts, Xspan, TriGard, Diamond Seal 2 and Invisi-Loc are trademarks of Cornerstone Specialty Wood Products, LLC™.