



ResinDek® Xspan®

ResinDek® Xspan® Product Description

ResinDek® Xspan® is a 1 1/8" thick panel that offers the look, maintainability and performance of ResinDek® in a structural flooring solution where a metal corrugated substructure is not required.

Tested and capable of supporting 125 p.s.f. dead loads at 32" center supports and 2,300 lb pallet jack loads (refer to product page for load span tables).

ResinDek® Xspan® flooring panels have been approved by IBC Code Officials for use as a structural flooring system in certain applications. Structural supports must be reviewed and approved by Cornerstone Specialty Wood Products, LLC (CSWP), and must be capable of supporting floor loads at specific intervals. For further details, call CSWP and/or your local building code official. All ResinDek® Xspan® panels are standard with a bright white back.

All ResinDek® panels are made with specially sorted and processed wood fibers, customized formaldehyde free resins, and a wax emulsifier. The ingredients are combined and compressed under extremely high pressure and temperature, resulting in a panel with superior physical properties that are especially designed and built to withstand heavy rolling cart and pallet jack loads.

ResinDek Xspan® Specifications

Mezzanine Floor Panels shall be ResinDek® Xspan® as manufactured by Cornerstone Specialty Wood Products, LLC (CSWP).

ResinDek® Xspan® shall be 1.125" in thickness and come standard with a bright white back and capable of supporting the designed weight capacities per the ResinDek® Xspan® load span tables. ResinDek® Xspan® shall have a Gray Diamond Seal 2™ or optional ResinDek® finish as provided by CSWP. A ten-year warranty shall be provided and passed to the end user from the manufacturer.

Installation of ResinDek® panels shall be in accordance with the ResinDek® Installation Instructions provided by CSWP.

ResinDek Options

- Gray Diamond Seal 2™ finish
- TriGard™ finish
- ESD
- Invisi-Loc® Underside Fasteners
- Collated Screws
- Custom T & G Configurations
- LEED® Credits can contribute towards LEED® qualified buildings
- Up to 4' x 10' T&G 4E Available



ResinDek Services

- Detailed CAD Layout Drawings
- Assistance with LEED information for ResinDek®
- Jobsite Installation Visits
- Comprehensive Sample Kits
- Industries Served Information
- Cut to Size Custom Panels Available

For detailed ResinDek® Xspan® Master Specifications please visit www.resindek.com, email info@resindek.com, or call CSWP 1-888-755-3048.



Job Name: _____ Job Location: _____

Qty	Product	T & G	Options	Tag #



©2016 Cornerstone Specialty Wood Products, LLC™
 All rights reserved. Cornerstone Specialty Wood Products, LLC, the Cornerstone logo, the 10-year warranty logo, ResinDek, The Panel of Experts, Xspan, TriGard, Diamond Seal 2 and Invisi-Loc are trademarks of Cornerstone Specialty Wood Products, LLC™.



12020 Tramway Drive
 Cincinnati, OH 45241
 Toll Free: 888.755.3048
 Tel: 513.772.5560
 Fax: 513.772.5561
www.resindek.com