


### Designed for Water Resistance

ResinDek WR flooring panels are perfect for self-storage facilities, modular offices, or any new construction project exposed to outdoor elements for up to 120 days. Their exceptional moisture resistance, meeting the stringent MR90 standard, ensures long-lasting durability, even in challenging environments - including interior applications with high humidity and limited washdown applications. ResinDek WR panels can be used on both mezzanines as well as the ground floor for AMR robotic applications.



### Eco-Friendly and Durable

Manufactured with mostly recycled and recovered wood fibers, ResinDek WR panels are not only environmentally conscious but also highly resistant to rot and termites. The panels are manufactured using environmentally friendly phenolic resins without added urea formaldehyde, ensuring a safer and healthier indoor environment. Other proprietary additives ensure the ResinDek WR panel's resistance to decay. ResinDek WR has been independently certified to be CARB compliant, conforming to SCS Recycled Content Standard V7-0.

### ResinDek® WR Specifications

Manufactured by Cornerstone Specialty Wood Products, LLC®, ResinDek WR shall be 0.75" thick and have the durability and structural integrity to support rolling pallet jack rolling loads up to 2,000 lbs with 20 GA B-Deck and AMR loads up to 500 lbs with 20 GA B-Deck. The panel shall feature a tongue and groove configuration along the two long edges. The recommended finish shall be determined based upon the type and volume of traffic traveling on the floor. **For detailed ResinDek WR Master Specifications please email or call Cornerstone Specialty Wood Products.**

### ResinDek® WR Quick Specs

**Panel Thickness:** 3/4"

**Panel Weight:** 3.09 psf

#### Pallet Jack & Product Load Limits

- Pallet jack rolling loads up to 2,000 lbs with 20 GA B-Deck

#### Mobile Robot & Product Load Limits

- AMR rolling loads up to 500 lbs with 20 GA B-Deck
- Robot contact pressure is 500 psi

### Available Finishes

#### For Heavy Equipment, Storage, Rolling Carts & Pallet Jacks

- Gray Diamond Seal® Coating
- Gray Diamond Seal® ESD Coating
- Unfinished

#### For AGV & AMR Robotic Traffic

- TriGard® ESD Coating
- TriGard® ESD Ultra Coating

### ResinDek® Options

- Invisi-Loc® Underside Fasteners
- Collated Screws
- Custom Tongue & Groove Configurations
- Available in sizes up to 4' x 8'

### Our Services

- CAD drawings that optimize materials
- Pre-job planning and on-site consultations
- Installation support for training
- Logistics support to coordinate deliveries
- Cut to size panels
- Custom testing for specific applications

### 10-Year Product Warranty

Cornerstone Specialty Wood Products, LLC® (CSWP) hereby warrants ResinDek WR panels to be free from defect, structurally sound, and able to safely carry the specified design loads. The warranty will flow through and transfer to the end user for the entire period of the warranty. Not intended for *permanent* outdoor exposure. Contact Cornerstone Specialty Wood Products for warranty details.